



Part Number:		DRAWN	0/12/2021
TE122	20E 2	CJ	8/13/2021
10122	305-2	CHECKED	8/13/2021
		P.D.	0/13/2021
Description:	anical Indicator	APPROVED	8/13/2021
Electro-Mech	anicai indicator	J.S.	0/13/2021

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions					
Min. Sound Pressure Level	83	dB (@ 10cm)					
Tone	Single						
Resonant Frequency	2,300	Hz	REVISION HISTORY				
Rated Voltage	5	V	REV	DESCRIPTION	DATE	APPROVED	
Voltage Range	3 ~ 6.5	V		Released from Engineering	10/21/2013	J.S.	
Max. Rated Current	30	mA	- 1	Updated drawing template, housing material, voltage	8/13/2021	P.D.	
Storage Temperature	-20 ~ +70	°C		range		P.D.	
Operating Temperature	-20 ~ +70	°C	NOTES				
Connection Method	PC Pins			All dimensions are in mm unless otherwise noted			
Mount Type	Thru Hole			2) All tolerances are ± 0.5 mm unless otherwise noted			
Housing Material	PBT		3) All parts meet RoHS				
Weight	2	a	4) Subject to change or redrawn without notice				