



		1		
art Number:		DRAWN	E /22 /2010	
TD202	3409-1	CJ	5/23/2019	
17393		CHECKED	5/28/2019	
		C.H.		
Description:	anadi iaar	APPROVED	F/20/2010	
Plezo II	ansducer	C.E.	5/28/2019	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions					
Min. Sound Pressure Level	104	dB (@ 10cm)					
Resonant Frequency	3,400	Hz		REVISION HISTORY			
Rated Voltage	9	V	REV	DESCRIPTION	DATE	APPROVED	
Voltage Range	3 ~ 15	V		Released from Engineering	10/21/2013	J.S.	
Max. Rated Current	9	mA		Updated to new template, temps, current, voltage range,	5/28/2019	C.F.	
Storage Temperature	-40 ~ +90	°C	7 1	dimensions, housing material		C.E.	
Operating Temperature	-40 ~ +85	°C		NOTES			
Connection Method	PC Pins			1) All dimensions are in mm unless otherwise noted			
Mount Type	Thru Hole			2) All tolerances are ± 0.5 mm unless otherwise noted			
Housing Material	PBT			3) All parts meet RoHS			
Weight	14 5	n		4) Subject to change or redrawn without notice			